

TECHCART[®]
TEACHING • TRAINING • MEETING



Are You Looking for best Camera for Classroom?



Are You Looking for best Interactive Panel?



Are You Looking for best Online Teaching Equipments?



Are You Looking for best Mic for Your Classroom?



Are You Looking for Easy, Reliable and best service?

- INTERACTIVE FLAT PANEL
- OPS
- PTZ CAMERA
- ACTIVE LED
- MICROPHONE
- AUDIO PODIUM
- DIGITAL PODIUM
- DESKTOP VISUALIZER
- DIGITAL SIGNAGE



Digital India
Power To Empower



available at
amazon





TECHCART[®] TC12HUL 4K PTZ CAMERA



Key Features

- 4K ULTRA HD (3840 x 2160)@60fps
- 12X Optical Zoom
- Leading Auto Focus Technology
- Double Streaming at the Same Time
- Gravity Sensor
- USB 3.0, HDMI, SDI, LAN
- Rich and Perfect Interface
- Multiple Presets (10 Presets by Remote)



CAMERA PARAMETER
Image Sensor : 1/2.5 Inch Ultra High Quality CMOS Sensor
Effective Pixels : 2.07 MP, 16:9
Video Format : 3840x2160, 2592x1944, 2560x1440, 1920x1080, 1280x720, 1024x576, 960x540, 800x448, 640x360 320x176
Optical Lens : 12X Optical Zoom, f=4.4mm-52.8mm
View Angle : 8.8° ~ 68.8°
Iris : F1.8-2.6
Digital Zoom : 16X
Low Illumination : 0.5 Lux (F 1.8, AGC ON)
DNR : 3D
White Balance : Auto / Manual / One Push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K / 6500K / 7000K
Focus : Auto / Manual / One Push
Electronic Shutter : Auto / Manual
BLC : On / OFF
WDR : OFF / Dynamic Level Adjustment
Video Adjustment : Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma Curve
Video SNR : >55dB

PTZ PARAMETER
Pan / Tilt Rotation : -170°+170°, -30°+ 30°
Pan / Tilt Controller Speed : 1.7~76 Second, 0.5~15 Second
Present Speed : Pan-60~Second, Tilt-30~Second
Present Numbers : 255 Presets (10 Presets by IR Remote)


USB CHARACTERISTICS
Support Operating : Windows 7 / Pro, Windows 8, Windows 10, Windows 11 / Pro, Windows XP, Mac OS, Linux
Video Compression : H.265, H.264, MJPEG
USB Communication : UVC Protocol

INTERFACE & PROTOCOLS
Video Output : USB 3.0 Type - B
Video Compression : H.264 AVC, H.264 SVC, H.265, MJPEG
Control Port : RS232 IN & OUT, RS485
Control Protocol : VISCA / Pelco-D / Pelco-P
Power Supply : HEC 3800 Outlet (DC 12V)

OTHER PARAMETER
Working Voltage : 12V
Working Current : 0.25A (Max)
Power Consumption : 2.5W (Max)
Storage Temperature : -40°C ~ 60°C -40°F ~ 140°F
Working Temperature : -10°C+40°C, 20%~80%
Dimension : 200mm x 176mm x 130mm (W x H x D)
Weight : 1.41 KG
Usage : Indoor Only
Package : Power Supply, USB 3.0 Cable, Remote Controller, User Manual
Accessories Optional : Mount (Extra Cost)

**Best for
Online / Hybrid Classes**

BOOK NOW



HYBRID CLASSROOM STUDIO SETUP



SMART CLASSROOM SETUP



TEHCART®

TH2010 PRO FHD PTZ CAMERA



Key Features

- FULL HD (1920 x 1080)@30fps
- 10X Optical Zoom
- Leading Auto Focus Technology
- Low Noise and High SNR
- Multiple Control Protocols
- USB 3.0
- Low Power Sleep Function
- Multiple Presets (10 Presets by Remote)



**1080P
FULL HD** 



CAMERA PARAMETER

Image Sensor : 1/2.9 Inch High Quality CMOS Sensor
Effective Pixels : 2.07 MP, 16:9
Video Format : 1920x1080P @30fps/25fps, 1280x720P @30fps/25fps, 1024x576P @30fps/25fps, 960x540P @30fps/25fps, 800x448P @30fps/25fps, 640x360P @30fps/25fps, 320x176P @30fps/25fps
Optical Lens : 10X Optical Zoom, f=4.34mm-41.66mm
View Angle : 8.8°~ 68.8°
Iris : F1.7-3.0
Digital Zoom : 10X
Low Illumination : 0.5 Lux (F1.8, AGC ON)
DNR : 2D & 3DDNR
White Balance : Auto / Manual / One Push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K / 6500K / 7000K
Focus : Auto / Manual / One Push
Electronic Shutter : Auto / Manual
BLC : On / OFF
WDR : OFF / Dynamic Level Adjustment
Video Adjustment : Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma Curve
SNR : >50dB

USB CHARACTERISTICS

Support Operating : Windows 7 / Pro, Windows 8, Windows 10, System Windows 11 / Pro, Windows XP, Mac OS, Linux
Video Compression : H.265, H.264, MJPG
USB Communication : UVC Protocol

INTERFACE & PROTOCOLS

Video Output : USB 2.0 Type-A
Video Compression : H.265, H.264, MJPG
Control Port : RS232 IN & OUT, RS485
Control Protocol : VISCA / Pelco-D / Pelco-P
Power Supply : HEC 3800 Outlet (DC 12V)

OTHER PARAMETER

Working Voltage : 12V
Working Current : 0.25A (Max)
Power Consumption : 2.5W (Max)
Storage Temperature : -10°C~+60°C, 20%~95%
Working Temperature : -10°C~+50°C, 20%~80%
Dimension : 156.8mm x 112.6mm x 139.5mm (W x H x D)
Weight : 1KG
Usage : Indoor Only
Package : Power Supply, USB 2.0 Cable, Remote Controller, User Manual
Accessories Optional : Mount (Extra Cost)

PTZ PARAMETER

Pan / Tilt Rotation : -170°+170°, -30°+ 90°
Pan / Tilt Controller Speed : 0.1-60 Second, 0.1-30 Second
Present Speed : Pan-60-Second, Tilt-30-Second
Present Numbers : 255 Presets (10 Presets on IR Remote)

Best for Online / Hybrid Classes

BOOK NOW



HYBRID CLASSROOM STUDIO SETUP



SMART CLASSROOM SETUP



TEHCART[®]

TH 3020

FHD PTZ CAMERA



Key Features

- FULL HD (1920 x 1080)@60fps
- 20X Optical Zoom
- Leading Auto Focus Technology
- Low Noise and High SNR
- Multiple Control Protocols
- HDMI, SDI, LAN
- Low Power Sleep Function
- Multiple Presets (10 Presets by Remote)



1080P
FULL HD



CAMERA PARAMETER
Image Sensor : 1/2.9 Inch High Quality CMOS Sensor
Effective Pixels : 2.07 MP, 16:9
Video Format : 1920x1080P @60fps/25fps, 1280x720P @60fps/25fps, 1024x576P @60fps/25fps, 960x540P @60fps/25fps, 800x448P @60fps/25fps, 640x360P @60fps/25fps, 320x176P @60fps/25fps
Optical Lens : 20X Optical Zoom, f=5.5mm-110mm
View Angle : 8.8°~ 68.8°
Iris : F1.7-3.0
Digital Zoom : 10X
Low Illumination : 0.5 Lux (F1.8, AGC ON)
DNR : 2D & 3D DNR
White Balance : Auto / Manual / One Push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K / 6500K / 7000K
Focus : Auto / Manual / One Push
Electronic Shutter : Auto / Manual
BLC : On / OFF
WDR : OFF / Dynamic Level Adjustment
Video Adjustment : Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma Curve
SNR : >50dB

PTZ PARAMETER
Pan / Tilt Rotation : -170°+170°, -30°+ 90°
Pan / Tilt Controller Speed : 0.1-60 Second, 0.1-30 Second
Present Speed : Pan-60-Second, Tilt-30-Second
Present Numbers : 255 Presets (10 Presets on IR Remote)


USB CHARACTERISTICS
Support Operating : Windows 7 / Pro, Windows 8, Windows 10, System Windows 11 / Pro, Windows XP, Mac OS, Linux
Video Compression : H.265, H.264, MJPG
USB Communication : UVC Protocol

INTERFACE & PROTOCOLS
Video Output : USB 2.0 Type-A
Video Compression : H.265, H.264, MJPG
Control Port : RS232 IN & OUT, RS485
Control Protocol : VISCA / Pelco-D / Pelco-P
Power Supply : HEC 3800 Outlet (DC 12V)

OTHER PARAMETER
Working Voltage : 12V
Working Current : 0.25A (Max)
Power Consumption : 2.5W (Max)
Storage Temperature : -10°C~+60°C, 20%-95%
Working Temperature : -10°C~+50°C, 20%-80%
Dimension : 150mm x 150mm x 167.5mm
Weight : 1.4 KG
Usage : Indoor Only
Package : Power Supply, USB 3.0 Cable, Remote Controller, User Manual
Accessories Optional : Mount (Extra Cost)

Best for
Online / Hybrid Classes

BOOK NOW



HYBRID CLASSROOM STUDIO SETUP



SMART CLASSROOM SETUP



TECHCART®

TH 490 4K PTZ CAMERA



Key Features

- 4K ULTRA HD (3840 x 2160)@30fps
- 4K Intelligence Dual Lens Camera
- 12X Optical Zoom
- 110° Ultra Wide FOC
- 6 Microphones Arrays, 6 mtrs Audio Range
- Intelligent Voice Tracking
- AI Smart Framing
- USB 3.0 Plug and Play Camera



CAMERA PARAMETER
Camera Lens : 4K Intelligence Dual lens
Effective Pixels : 851M, 16:9
Video Format : 3840x2160, 2592x1944, 2560x1440, 1920x1080, 1280x720, 1024x576, 960x540, 800x448, 640x360 320x176
Optical Lens : 12X Optical Zoom, f=3.4mm-40.3mm
View Angle : 7.6° ~ 80.5°
Iris : F1.8-2.6
Digital Zoom : 15X
Low Illumination : 0.5 Lux (F 1.8, AGC ON)
DNR : 2D & 3D
White Balance : Auto / Manual / One Push / Specified Color Temperature
Focus : Auto / Manual / One Push
Video Adjustment : Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma Curve
Video SNR : >55dB
Paranormic Lens : Fixed Focus
Iris : F2.0+5%
Focus : F=1.89mm

INTERFACE
Back Panel : HDMI, LAN, USB 3.0, A-In, RS232-In, DC 12V Power
Video Output : USB 3.0, HDMI, LAN
Video Compression : LAN - H.264, H.265, USB - H.265, MJPEG
Control Port : RS232 IN
Control Protocol : VISCA / Pelco-D / Pelco-P
Power Supply : HEC 3800 Socket (DC 12V)
Audio Input : Dual Channel 3.5mm Linear Input
Audio Output : HDMI, LAN, USB 3.0
Audio Compression : ACC, MP3, G.711A
Network Protocols : RTSP, RTMP, ONVIF, GB/T28181, VISCA OVER IP, IP VISCA, RTMPS, SRT, Support remote upgrade, Remote restarting and Remote reset
Power Adapter : Input - AC 110V-AC 220V Output - DC 12V / 2.5 A

OTHER PARAMETER
Rotating Angle : Pan +110° Tilt - -30°+30°
Control Speed : Pan 0.1/s-100/s Tilt 0.1/s-70/s
Smart Framing : Group Framing, Face Detection
Voice Tracking : Voice Localization, Voice Tracking On/Off
Microphone : 6 Mics arrays with 6meters audio range
Product Dimensions : 220x114x159 mm (L x W x D)

Best for Video Conferencing

BOOK NOW



6 METERS AUDIO RANGE



PANORAMIC + CLOSE UP LENS



TECHCART[®] TW 400K



Key Features

- 4K ULTRA HD (3840 x 2160)@30fps
- EPTZ and 4X Digital Zoom
- 126° wide field of view
- AI-powered Auto Framing
- USB 3.0 main and Sub Dual Stream Outputs
- Built in Microphone
- 2D & 3D DNR
- Plug and Play with USB 3.0



CAMERA PARAMETER
Min Illumination : 0. Lux (F 1.8, AGN ON)
Lens : f=2.72 mm
Aperture : F 2.5
Digital Zoom : 4X
DNR : 2D and 3D
Ultra-low Illumination : On / Off
White Balance : Auto / Manual / One Push / 3000K / 3500K / 4000K / 5000K / 5500K / 6000K / 6500K / 7000K
Focus : Auto / Manual / One push focus (Available on AM series)
Exposure : Auto / Manual
Auto Framing : On / Off / Sensitivity
Backlight Compensation : On / Off
Dual Stream : On / Off
SNR : >55dB

USB FEATURES
Operating System : Windows 7, Windows 8.1, Windows 10, MacOS, Linux (Require to support UVC)
Video Format : YUY2, MJPG, H.264, H.265
Audio Over USB 3.0 : Support
USB Protocols : UVC, UAC
PTZ Control : Support EPTZ
Hardware Requirement : 2.4GHz Intel Core Duo Processor or Higher " 2GB RAM or more " USB 3.0, (USB 3.0 needed for 4K)

OTHER PARAMETERS
Input Voltage : 5V
Input current : 1A (max)
Power Consumption : 5W (max)
Store Temperature : -10 C - +60 C
Store Humidity : 20% - 90%
Working Temperature : -10 C - +50 C
Working Humidity : 20% - 80%
Dimension (WxHxD) : 222x93.25x56.5 mm
Weight : Around 0.53 Kg
Application : Indoor
Accessory : User Manual, Remote Control, USB 3.0 Cable

**Best for
Video Conferencing**

BOOK NOW



VIDEO CONFERENCING



CAMERA FEATURES



TECHCART[®]

TW 300



Key Features

- FULL HD (1920 x 1080)@30fps
- EPTZ and 4X Digital Zoom
- 88° wide field of view
- Built in 2 Microphones 1+ mtr Voice Pickup
- Noise Canceling Technology
- Adjustable Video Settings, Brightness, Etc
- Support all Major third-party Platforms
- USB 2.0 Plug add Play



**1080P
FULLHD**



CAMERA PARAMETER
Image Sensor : High Quality CMOS Sensor
Effective Pixels : 2 MP, 16:9
Video Format : 960x540, 320x180, 432x240, 640x360, 800x448, 800x600, 864x480, 960x720, 1024x576, 1280x720, 1600x896, 1920x1080, 272x144, 368x208, 384x216, 480x272, 624x352, 912x512
USB : USB 2.0 (for power and firmware upgrade)
View Angle : 88° (D) / 80° (H) / 50° (V)
Compatible : Support all major third-party platform
Low Illumination : 0.5 Lux (F 1.8, AGC ON)
Lens Focus : Fixed
Distance Range of Lens : 0.3m - 1.7m
Backlight Contrast : On / Off
Anti-Flicker : Manual
Video Adjustment : Brightness / Resolution / Saturation / Contrast / Gain / Low-light / Exposure / White Balance


CAMERA PARAMETER
SNR : >50dB
Input Voltage : 5V
Input Current : 500mA (max)
Power : 2.5W (max)
Temperature : Storage : -10 C - +60 C Operating : -10 C - +50 C
Humidity : Storage : 20% - 95% Operating : 20% - 80%
Cable Length : 1.8 meters
Dimension : 102x46x30 mm
Weight : 0.15 Kg

Best for Video Conferencing

BOOK NOW



VIDEO CONFERENCING



CAMERA FEATURES



TECHCART®

INTERACTIVE FLAT PANEL

Z-7500



Key Features

- 4K ULTRA HD Resolution
- Front Audio Stereophonic Speakers
- Industrial Grade Aluminium
- Multiple Ports Input HDMI, VGA, Video, touch
- IFR Touch Technology for Smooth Writing
- 20 Touch Points <5~8ms Response
- 3mm Protect Glass and Anti Scratch
- Support Apk Install and Authorize Management
- RAM 4 / 8 GB
- ROM 32 / 128 GB

WITH NOTE WRITING SOFTWARE



4K ULTRAHD

PANEL
Panel Size : 75"
Respond Time : 4ms
Visual Ratio : 16:9
Panel Type : LG IPS Panel
Resolution : 3840 x 2160
Pixel Pitch : 0.4296 x 0.496 mm
Frequency : 60Hz
Display Colors : 1.07B (10 Bit)
Color Stability : 72%
Contrast Ratio : 4000:1
Light Source : DLED
Life Span : >50000hrs
Brightness : 400cd / m2

REAR INTERFACE
HDMI : 2, 1 Output
USB 2.0 : 1
USB 3.0 : 2
USB Touch Port : 1
Audio In : 1
Line Out : 1
Optical Out : 1
Frequency : 60Hz
Display port : 1
VGA Input Port : 1
Type C Port : 1
RS232 : 1
LAN Rj45 : 1 In and 1 Out

TOUCH PARAMETER
Touch Specifications : Non-Contact IFR Sensing Technology
Support Systems : Windows 7, 8, 10, XP, Android Linux, Mac OS , Chrome
Touch Points : 20 Points Touch
Min Identifier : 2mm
Input Mode : Opaque Object (Finger, Pen & Touch)
Respond Time : >10ms
Touch Depth : +1mm
Writing Height : >3mm
Writing Display : Single Stylus Pen Two-Color
Output Co-ordinates : 32767 x 32767

STRUCTURE
Bare Dimension : 1709x1020x88mm
Packing Dimension : 1860x220x1160 mm
Machine + Wall Mount Thickness : 118mm
VESA Hole Site : 800x400 mm
Wall Mounting Screw : M8 x 25 mm
Net weight : 58 Kgs
Gross Weight : 68 Kgs

SYSTEM
System Version : Android 13
CPU : Quad Core A55 2.1 Ghz
GPU : Mali G52MP2
RAM : 4GB / 8GB
ROM : 32 / 128 GB

AUDIO-VIDEO PARAMETERS
Speakers : Sound Track-2.0
Power-2x20 W

WIRELESS
Bluetooth : Version-5.0
Working Frequency-2.4 Ghz
Working Distance-0-10m
Remark-via the wireless Module SI07B
Wifi : Version - 802.11 ac/b/g/n/a/ax
Working Frequency-2.4 Ghz/5Ghz
Working Distance-Upto 10meters
Remark-Via the Wireless Module SI07B

POWER
Voltage : 100-240V-50/60Hz 4A
Max Power Consumption : 350W
Standby Power Consumption : >0.5W

POWER
Voltage : 100-240V-50/60Hz 4A
Max Power Consumption : 350W
Standby Power Consumption : >0.5W



65" 75" 86" 98" AVAILABLE IN DIFFERENT SIZES

Best for Online & Hybrid Classes

BOOK NOW





TECHCART[®]

Open Pluggable Specification

OPS



Open Pluggable Specification

OPS

Key Features

- Pre-installed Windows 10
- Processor : Intel[®] 10th/11th Gen Core™ i5 / i7
- 8 GB RAM (Upgradable to 32 GB)
- 512 GB SSD (Upgradable to 1 TB)
- 5 USB 3.0 and 1 USB 2.0
- DP Port, HDMI Support / Rear 80 Pins Support
- Wifi Yes and Bluetooth Yes
- Support OS - Windows 10 / Windows 11
- Slim and Compact Design Takes Up Less Space
- Type C, USB, LAN, 3.5mm Audio In + Out, 3.5mm Microphone In
- Metal Finish Design
- Available in **ASIAN** and **EURO**
- Power Input : 12-19 V DC In
- Net Weight : 1 Kg



Scan to Order

**Best for
Smart Teaching**

BOOK NOW





TECHCART[®]

AP-6000

AUDIO PODIUM



Key Features

- Built in 3 Subwoofers and 1 Tweeter 60 Watt
- Gooseneck Microphone
- LED Reading Lamp
- 1 Handheld and 1 Collar Microphone
- Built in Control Panel and 24V Phantom
- Smart and Robust Design
- 1 Aux Input Control
- Short Circuit Clipping and High Temp Protection



Scan to Order

TECHNICAL SPECIFICATION

Power Output	60 Watts
Input Channels	Mic-1 (Gooseneck Mic) 8mV, Mic-2 : 4mV, Line-100mV, AUX-200mV
Frequency Response	50 - 16,000Hz
Tone Control	Bass ± 5 dB at 100Hz, Treble ± 5 dB at 10k Hz
MIX Output	775mV
Digital Player	MP3 Recorded Player with USB, SD, MMC Card & Bluetooth
USB Charger Outlet	DC-5V, 1A
External Speaker Impedance	4 Ω to 8 Ω
Power Supply	AC 220-240V, 50/60Hz
Power Consumption	AC 100VA
Dimensions	L580 x W420 x H1100 mm
Weight	30 kg
Microphone	1 Handheld and 1 Collar Microphone
Microphone Element	Dynamic, Cardioid
Transmission Distance	15-30 Meters
RF Output Power	15mW
Frequency Response	50 - 15,000Hz
Power Requirement	3V (2x1.5V AA Pencil Cells)
Current Consumption	<100 mA
Weight (w/o Battery)	180 gm

Best for **BOOK NOW**
Teaching / Training / Meeting



**GOOSENECK MIC &
LED LIGHT**



**3 SUBWOOFERS &
1 TWEETER SPEAKER**



**INPUTS &
OUTPUTS**



**1 HANDHELD MIC &
1 COLLAR MIC**



TEHCART®

Multimedia Digital Podium

TCDP 1099



Key Features

- One Stop Solution for Modern Day
- Touch Screen with Sliding Lockable Cover
- Motorised Up-Down & Stop Panel
- Built in Audio Complete System
- Built in Latest Configuration CPU (Opt)
- Built in Digital Visualizer (Opt)
- Built in Central Controller
- Built in Wheels for Easy Movement



METALLIC BODY
Mild Steel with locable wheels
Sliding Top opening can be used as a laptop tray acting as shelves for supporting extra equipments (Laptop or documents camera) with Lock in the Centre
Doors with Lock
Storage Rack with Lock
Keyboard & Mouse tray
With Wheels
External Connectors on the side
VGA - 1, USB - 1, RJ45 - 1, To Connect Laptop, Documents Camera USB, Etc

SYSTEM DETAILS
Chasis : Industrial Grade Aluminium Chasis
Processor : i3 / i5 / i7 (6th Generation)
Memory : 4GB / 6GB / 16GB
HDD / SSD : 256GB / 512GB / 1 TB
Operating System : Window 11 Pro
Minimum Range : 15 Meters
Power Supply : 100-240V, 50HZ, AC Supply
Provision for : A dedicated space to house CPU/Laptop Additional with Security Lock Tray, Sliding Shelf for Devices Visualiser, Space for Keyboard & Mouse

INTEGRATED AUDIO
Gooseneck Microphone : 2
Cordless Handheld Microphone : 1
Collar Cordless Microphone : 1
Amplifier : Dual Channel 60W / 80W / 100W
Speaker : Wall Mount Speaker (20x2 / 4 / 6) Watt Each

INTEGRATED INTERACTIVE PANEL
Interactive Panel with Motorised Angle Adjustment / Tilt / Up & Down movement by Button / Switch
22" Inch, 10 Point Touch Screen Monitor, Finger Touch & Pen Touch Features
Resolution : 1920 x 1080 FHD
Dynamic Contrast ratio : 50M:1
Brightness : 200cd/m ² (typ)
Colors : 16.7M
Aspect Ratio : 16.9
Interface : USB
Refresh Rate : 60 Hz
VGA : 1
USB 3.2 Type - A Down Stream : 2
USB 3.2 Type - B Up Stream : 1
3.5mm Audio In : 1
3.5mm Audio Out : 1
HDMI 1.4 : 1
Display Port : 1

CENTRAL TOUCH CONTROL SYSTEM
Projector : On
Projector : Off
Screen : Up
Screen : Down
Volume : Up
Volume : Down
Volume : Mute
Source Selection : Computer Laptop, Visualizer, DVD/VCR
Microphone Control - Gooseneck x 2
Microphone Control - Cordless
DVD/VCR - Controls
Play, Forward, Rewind, Stop, Pause, Recording
Front Logo
Lockable Wheels

Best for **BOOK NOW** Lecture & Conference room



DOCUMENT CAMERA




TOUCH MONITOR



MINI PC



AMPLIFIER WITH MIC



PODIUM CONTROLLER



TECHCART[®]

Digital Signage



Digital Signage

Key Features

- 55" Floor Mount Non-Touch Metal Body signage
- 4K Ultra HD Resolution
- Wide Viewing Angle of 178°
- 4mm, MOHS 7 Grade Tempered Glass, Shatter Proof
- Including pictures, audio, video, PDF, Etc
- Built in Android and DSS Apk
- Works with LAN, Wifi
- 3-level check of programs, and schedules
- Built for 24x7 Performance with 60000hrs Screen Life
- Eco LED backlit for Power Saving
- DSS Management Software to manage <200pcs DSS Players



Scan to Order

Best for **BOOK NOW**
Commercial Advertisement





TEHCART[®]

Active LED



Active LED

Key Features

- 4K Ultra HD Resolution
- 100,000 hours of 24/7 Operation
- Multiple Support MP4, JPG, PNG, PDF, PPT
- Support HDMI, USB
- High Quality Indoor and Outdoor LED Display
- Split Screen to showcasing different Ads
- Increased reliability easier to maintain and have a longer life with the latest technology
- Complete front access for easy installation and service
- Full range of optional processing and content management technologies
- Includes necessary video wall controllers with scaling and image processing
- On-board redundant power supply with automatic failover to maximize uptime



Scan to Order

Best for **BOOK NOW**
Commercial Advertisement





TECHCART[®] TCDC-550



Key Features

- Effective Pixels >500/800 Millions
- Fixed Focus (Digital Zoom)
- Built in High Sensitivity Digital Microphone
- Vertical and Horizontal Shooting Direction
- A4 and A3 Sizes
- Touch Sensors
- Power <2W
- USB Plug and Play



SPECIFICATIONS


Effective Pixels	500 / 800 Pixels (Optional)
Focusing Method	Fixed Focus (Digital Zoom)
Definition	100 Lines
White Balance	Automatic
Frame Rate	15 Frames (3264 x 2448) / 20 Frames (2592 x 1944) / 30 Frames (1920 x 1080)
Shooting Range	A4 (310 x 220), A3 (Optional)
Port	DC 5V / USB Output, 3.0 B Port 1
Output	USB 3.0 MJPG
3D Noise Reduction	Yes
Physical Button Function	No
Illumination	High Brightness LED x 10 Grains, Brightness Level : Level 3 , Touch
Lightning Control	Four Level Cycle Control of Touch Support
Recording	Built in High Sensitivity Digital Microphone
Power	USB 5V
Net Weight	<2W
Gross Weight	1 KG
Packing Specification	12cm x 22cm x 46cm (Width x Height x Length)
Packing Enclosure	Warranty Card, Certification of Conformity, 2m A/B Cable, Document Pad
Cabinet Material	Aluminium Alloy + Environmentally Friendly ABS Plastic
Body Specification	10cm x 9.5cm x 32.5cm (Width x Thickness x Height)
Expanded Size	10cm x 27cm x 32.5cm (Width x Thickness x Height)
Software	Random Software Teaching Booth V2.0 Version
Software Function	Annotation, Same-Screen Comparison, Partial Reading, 360° Rotation, Picture-in-Picture, Etc
Software Language	Simplified Chinese (English Version Available)



Scan to Order

Best for Teaching / Smart Classes

BOOK NOW



LEADING EDUCATIONAL MULTIMEDIA
TECHNOLOGY AND SOLUTION PROVIDER
TCDC - 550

SMART CLASSROOM



CAMERA MONITORING



TECHCART[®]

Desktop Visualizer GK-9802



Key Features

- 8 Mega Pixels
- 10x Digital AI Zoom
- 32 Images Storage
- Auto Focus
- Double Side LED and Base Light
- Inputs - HDMI, VGA, Video, Audio (Opt)
- Outputs - HDMI, VGA, Video
- Remote Control and Touch Control Panel
- One Button Adjustment, Image Freezing
- Split Screen, Automatic White Balance



SPECIFICATIONS

Lens	22-26x Optical Zoom, 10x Digital AI Zoom, 8 Mega Pixels
Storage	32 Images
Focus	Automatic
Shooting Range	A4 and A3 Sizes
Light	Double Side LED Light, Base Light
Input	(Standard Version) VGA, 1 Video, 1 Audio (Optional) USB - 1 / (HD Version) VGA, 1 HDMI, 1 USB
Output	(Standard Version) VGA, 1 Video, 1 Audio (Optional) USB - 1 / (HD Version) VGA, 1 HDMI, 1 USB
Control	RS-232, USB
Definition	1200 TV Line
Net Weight	5KG
Gross Weight	6.5KG
Product Size	470x370x135mm (Closed) / 410x375x550mm (Opened)
Packaging Size	440x200x550mm
Control Mode	Remote Control
Digital Function	Mirror / Color - Black & White / Rotation / One Button Adjustment / Slit Screen / Image Freeze / Color Adjustment / Automatic WhiteBalance



Scan to Order

Best for Teaching / Smart Classes

BOOK NOW





TECHCART®

DSP 0808 Pro



Key Features

- Studio Quality (16Bit/48kHz) Recording
- Features 2 Input and 2 Output Mic/Line
- Extreme Low-Latency Digital Streaming
- Switchable Phantom Power
- Support Windows/Android and Mac IOS
- Compatible with Popular DAW Softwares
- USB 2.0 Bus-powered
- Compact Durable Aluminum Body



LINE INPUTS
Type : 2 x 6.3mm TRS, Balanced
Input Impedance : 18K
THD+N : <0.5%
S/N Ratio : >55dB
Input Level : 3mV + 1mV, 25mV PAD On +5mV
Phantom Power ; +48 VDC at both XLR female only

MICROPHONE INPUTS
Type : Combo XLR female x 2
Frequency Response : 30Hz to 20kHz
Input Impedance : 2.2k
THD+N : <0.5%
S/N Ratio : >55dB
Input Level : 3mV + 1mV, 25mV PAD On +5mV
Phantom Power ; +48 VDC at both XLR female only

DIGITAL AUDIO
Bit Depth : 16 bit
Internal Sample Frequency Selection : 44.1, 48kHz
Power : USB bus-powered
Dimensions : W175 x H58 x D123 mm
Accessories : 1 x USB A+B Cable
Weight : 615g approx

INSTRUMENT INPUTS
Type : 2 x 6.3mm TRS, Balanced
Input Impedance : 1M
Frequency Response : 20Hz to 20kHz
Input Level : 3.50mV + 1mV, 30mV PAD ON + 5mV

HEADPHONE OUTPUT
Type : 6.3mm active stereo
Maximum Output : 300mV/ch.@ 8 load

OUTPUT L & R
Type : 2 X 6.3mm female, unbalanced
Maximum Output : 550mV

Best for
Online Classes & Audio Recording

BOOK NOW





TECHCART[®]

SENNHEISER

XSW1-ME2



Key Features

- Clip-on Microphone & Bodypack Transmitter
- Antenna-switching Diversity Reception
- Integrated Antennas
- Auto frequency Management & Synchronization via Remote Channel for Easy Setup
- UHF Frequencies within a Large Bandwidth
- Upto 10 Compatible Channels
- Easy-to-use Wireless Collar Microphone



SPECIFICATIONS

Max Sound Pressure Level : 130dB SPL
Sensitivity in Free Field, No Load : 1.6mV/Pa
Frequency Response : 50Hz-16kHz
Frequency Range : 548-572 MHZ
Simultaneous Channels : Up to 10 Channels
Operating Range : 250 ft Line of Sight
Microphone Included : YES
Microphone Type : Condenser
Channel Selection : Automatic
Polar Pattern : Cardioid
Connection Cable : Locking mini-jack
Microphone Cable Length : 5.2ft
Signal/Noise Ratio : >103dB
Dimensions : 7.87 x 1.65 x 5 Centimeters

Promoted by Techcart



Best for
Online Classes & Audio Recording

BOOK NOW



COLLAR MIC



RECEIVER FRONT



RECEIVER BACK



**BODYPACK
TRANSMITTER**



TECHCART®

SENNHEISER

XSW1-ME3



Key Features

- Light Weight Headmic & Bodypack Transmitter
- Antenna-switching Diversity Reception
- Integrated Antennas
- Auto frequency Management & Synchronization via Remote Channel for Easy Setup
- UHF Frequencies within a Large Bandwidth
- Upto 10 Compatible Channels
- Easy-to-use Wireless Headset System



SPECIFICATIONS

Max Sound Pressure Level : 150dB SPL
Sensitivity in Free Field, No Load : 1.6mV/Pa
Frequency Response : 50Hz-16kHz
Frequency Range : 548-572 MHZ
Simultaneous Channels : Up to 10 Channels
Operating Range : 250 ft Line of Sight
Microphone Included : YES
Microphone Type : Condenser
Channel Selection : Automatic
Polar Pattern : Cardioid
Connection Cable : Locking mini-jack
Microphone Cable Length : 1.6 Meters
Signal/Noise Ratio : >103dB
Dimensions : 34.8 x 34.5 x 8.6 Centimeters

Promoted by Techcart



Best for
Online Classes & Audio Recording

BOOK NOW



HEADSET MIC



RECEIVER FRONT



RECEIVER BACK



**BODYPACK
TRANSMITTER**



TECHCART®



YAMAHA

YVC-200



Key Features

- Yamaha's professional Quality DSPs
- Super Wideband Audio for ample, Clear Sound
- 360 and max radius 2m Mic Pick up Range
- Maximum 88dB Loud Speaker Volume
- USB Connection for Laptop
- Bluetooth/NFC Connections for phones & Tablets
- Rechargeable Battery for Upto 10 hours use
- User Friendly Touch Sensor Buttons



Promoted by Techcart



GENERAL
Recommended Use : Up to 4 People
Interfaces : USB 2.0 Full Speed (Mini-B), Bluetooth, NFC (Near field Communication), 3.5mm Headset Jack (Stereo Out/Monaural In)
Connectable : USB Computer running windows or Devices macOS
Bluetooth : Smartphone running Android or iOS
Power Sources : USB bus power
Maximum Power Consumption : 2.5W
Dimensions (WxHxD) : 140x43x140mm
weight : 0.28 Kg
Color : Black, White
Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later
Bluetooth : Version 4.2
NFC : Compatible to Android devices
Accessories : USB Cable 1m, User Manual, Carrying case
Operating Environment : Temperature 0 to 40 C Humidity 20 to 85% (No Condensation)
Storage Environment : Temperature -20 to +50 C Humidity 10 to 90% (No Condensation)
Others : Auto standby energy-saving function, Firmware update, Security slot

AUDIO
Microphone : Omnidirectional microphonx1, 360 coverage
Speaker : 45mm Full-range speaker x 1
Volume : Momentary maximum 88dB (0.5 m)
Frequency Bandwidth : Sound Pickup 150 Hz to 16,000 Hz Playback 200 Hz to 16,000 Hz
Signal Processing : Adaptive echo canceller, Noise reduction, Auto tracking, Auto gain control, Human Voice Activity Detection (HVAD)
Radio Interference Standard : FCC, VCCI Class B

Best for Audio / Video Conferencing

BOOK NOW



360° HD Audio with Omni-Directional Sound

WIRELESS VIDEO CONFERENCING



VIDEO CONFERENCING



TECHCART®



YAMAHA

YVC-330



Key Features

- Comfortable Meeting in a Noisy Environment
- Light Weight Design Powered by USB
- Echo Canceller and Clear Conversation
- 3 Microphones with Human Voice Detection
- USB Powered Rich Speakers Volume
- Daisy Chain 2 Units for Medium Sized Room
- Plug and Play, Bluetooth, NFC and Audio In/Out
- Compatible with any UC Applications



Promoted by Techcart

GENERAL	
Interfaces : USB 2.0 Full Speed (Mini-B), Bluetooth, NFC (Near field Communication), EXT In/Out (Stereo mini plug)	
Connectable : USB Computer running windows or Devices macOS Bluetooth : Smartphone running Android or iOS	
Power Sources : USB bus power Maximum Power Consumption : 2.5W	
Dimensions (WxHxD) : 235x46x226mm weight : 0.8 kg	
Color : Black	
Support OS : Windows 10, Windows 8.1, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later	
Bluetooth : Version 2.1 + EDR	
NFC : Compatible to Android devices	
Accessories : USB Cable 3m, User Manual	
Operating	: Temperature 0 to 40 C
Environment	Humidity 20 to 85% (No Condensation)
Storage	: Temperature -20 to +50 C
Environment	Humidity 10 to 90% (No Condensation)
Others : Firmware update (Transferred from x3, 360 coverage)	

AUDIO	
Microphone : Unidirectional microphones x3, 360 Coverage	
Speaker : Full-range speaker x 1	
Volume : Momentary maximum 91dB (0.5 m)	
Frequency Bandwidth : 190 Hz to 20,000 Hz	
Signal Processing : Adaptive echo canceller, Noise reduction, Auto tracking, Auto gain control, dereverberation, Sound cap	
Standard mode : Pick-up the sound in small-medium conference rooms	
Sound cap : Auto mute distracting noise in open work place and deliver only the sound from the pick-up range (Radius of 1 m) * 2 units daisy chain connection is available on Standard Mode	

OPTIONAL ACCESSORY	
Daisy chain cable (Product number : YCBL-DC3M, Cable length-3m, Terminal shape-stereo mini plug x2)	

Best for Audio / Video Conferencing

BOOK NOW



VIDEO CONFERENCING



DAISY CHAIN



TECHCART[®]



YAMAHA

YVC-1000




Key Features

- Comfortable Meeting in a Noisy Environment
- Light Weight Design Powered by USB
- Echo Canceller and Clear Conversation
- 3 Microphones with Human Voice Detection
- USB Powered Rich Speakers Volume
- Daisy Chain 2 Units for Medium Sized Room
- Plug and Play, Bluetooth, NFC and Audio In/Out
- Compatible with any UC Applications



GENERAL
Interface : Control unit USB 2.0 High Speed, Bluetooth, Audio Input/Output terminal (stereo RCA pin), External speaker terminal (RCA pin) x2 Power terminal, Microphone terminal Microphone Input/Output terminals
Power consumption : 20W (One Connected Microphone) 35W (Five Connected Microphones)
Radio Interface : FCC (Part 15B) Class A, ICES-003 standard
Operating environment : Temperature - 0 to 40 C Humidity - 20 to 85%
Dimensions : Control unit (WxHxD) 332x95x165 mm Microphone (WxHxD) 136x36x136 mm
Weight : Control unit 1.8 Kg Microphone 0.4 Kg
Power source : 120V (60Hz)
Support OS : Windows 10, Windows 11, USB 2.0, USB 3.0 or later
Bluetooth : Version 2.1 + EDR Maximum distance 10m
NFC : Compatible to Android devices
Accessories : Power cable 3m, USB cable 5m, Microphone cable 5m, Quick Start Guide

AUDIO
Microphone : Unidirectional microphones x 3
Speaker : Full-range x 1
Volume : 95dB (0.5 m)
Frequency Bandwidth : 100 Hz to 20,000 Hz (For Souch Pickup and Playback)
Signal Processing : Adaptive echo canceller, Noise reduction, Auto tracking, Auto gain control, dereverberation, Auto room EQ, Auto audio tuning



Promoted by Techcart



Best for
Audio / Video Conferencing

BOOK NOW

Front

● Control Unit

● Microphone



332 mm (13-1/16")

95 mm (3-3/4")

136 mm (5-3/8")

36 mm (1-7/16")

Top side

● Control Unit

● Microphone



162 mm (6-3/8")

136 mm (5-3/8")

Terminals

● Control Unit

● Microphone



- 1 Power terminal
- 2 USB port
- 3 Microphone terminal
- 4 External speaker terminals (AUDIO OUT)
- 5 Audio output terminals (AUDIO OUT)
- 6 Audio input terminals (AUDIO IN)
- 7 Input terminal (IN)
- 8 Output terminal (OUT)



TEHCART[®]

Floor Stand



Floor Stand

Key Features



- Interactive Panel / TV Size 55" - 110"
- Strong heavy duty material
- Loading Capacity 110 Kgs
- Laptop / Camera VC Shelf Yes
- TV Height Adjustable
- With Lockable caster wheels, Wheel lock Yes
- High grade cold rolled steel
- Product Size : 1330 x 660 x 1820mm
- Universal VESA worldwide standard : 900 x 600
- Heavy-duty 360° swivel casters
- Strong heavy duty model to make sure your LED TV lies in safe hands



Scan to Order

Best for
Interactive Flat Panel Display

BOOK NOW



Our Happy Teachers, Schools & Institutions

Marketed & Distributed by :

Techcart Integrated Solutions Pvt. Ltd.

133, Manas Kunj, Uttam Nagar, New Delhi-110059

011- 46514545, +91 9910600023

www.techcartintegration.com

sales@techcartintegration.com, techcartintegration@gmail.com



Weight and dimensions shown are approximate and appearance specifications / optional feature varies from model to model are subject to change without prior notice. Product may be subject to export control regulations. Windows, Powerpoint, Excel and Word are trademarks of Microsoft Corporation. Android is a registered trademarks of google Inc. HDMI, HDMI logo and High Definition Multimedia interface are registered trademark of HDMI Licensing LLC. All Trademark are the property of their respective trademark owners.

Dealers & Distributors

- Lucknow
- Mumbai
- Hyderabad
- Pune
- Kolkata
- Kochi
- Jaipur
- Ahemdabad
- Bangalore
- Chandigarh
- Indore
- Dehradun
- Coimbatore
- Patna