



Key Features

- Built in 3 Subwoofers and 1 Tweeter 90 Watt
- Gooseneck Microphone
- LED Reading Lamp
- 1 Handheld and 1 Collar Microphone
- Built in Control Panel and 24V Phantom
- Smart and Robust Design
- 1 Aux Input Control
- Short Circuit Clipping and High Temp Protection

TECHNICAL SPECIFICATION	
Power Output	90 Watts
Input Channels	Mic-1 (Gooseneck Mic) 8mV, Mic-2 : 4mV, Line-100mV, AUX-200mV
Frequency Response	50 - 16,000Hz
Tone Control	Bass ± 5 dB at 100Hz, Treble ± 5 dB at 10k Hz
MIX Output	775mV
Digital Player	MP3 Recorded Player with USB, SD, MMC Card & Bluetooth
USB Charger Outlet	DC-5V, 1A
External Speaker Impedance	4Ω to 8Ω
Power Supply	AC 220-240V, 50/60Hz
Power Comsumption	AC 100VA
Dimensions	L580 x W420 x H1100 mm
Weight	30 kg
Microphone	1 Handheld and 1 Collar Microphone
Microphone Element	Dynamic, Cardioid
Transmission Distance	15-30 Meters
RF Output Power	15mW
Frequency Response	50 - 15,000Hz
Power Requirement	3V (2x1.5V AA Pencil Cells)
Current Consumption	<100 mA
Weight (w/o Battery)	180 gm

Best for BOOK NOW Teaching / Training / Meeting



Scan to Order

C. TECHCART







www.techcartintegration.com