



Key Features

- 4K ULTRA HD (3840 x 2160)@30fps
- EPTZ and 4X Digital Zoom
- 126° wide field of view
- Al-powered Auto Framing
- USB 3.0 main and Sub Dual Stream Outputs
- Built in Microphone
- 2D & 3D DNR
- Plug and Play with USB 3.0

CAMERA PARAMETER
Min Illumination : 0. Lux (F 1.8, AGN ON)
Lens : f=2.72 mm
Aperture : F 2.5
Digital Zoom : 4X
DNR : 2D and 3D
Ultra-low Illumination : On / Off
White Balance : Auto / Manual / One Push / 3000K / 3500k
/ 4000K / 5000K / 5500K / 6000K / 6500K
/ 7000K
Focus : Auto / Manual / One push focus
(Available on AM series)
Exposure : Auto / Manual
Auto Framing : On / Off / Sensitivity
Backlight Compensation : On / Off
Dual Stream : On / Off
SNR : >55dB

	USB FEATURES
Γ	Operating System : Windows 7, Windows 8.1, Windows 10,
	MacOS, Linux (Require to support UVC)
1	Video Format : YUY2, MJPG, H.264, H.265
7	Audio Over USB 3.0 : Support
Ī	USB Protocols : UVC, UAC
ł	PTZ Control : Support EPTZ
ł	Hardware Requirement : 2.4GHz Intel Core Duo Processor
	or Higher " 2GB RAM or more "
	USB 3.0, (USB 3.0 needed for 4K)
(OTHER PARAMETERS
h	Input Voltage : 5V
h	Input current : 1A (max)
	Power Consumption : 5W (max)
	Store Temperature : -10 C - +60 C
	Working Temperature : -10 C - +50 C
	Working Humidity : 20% - 80%
⊢	Dimension (WxHxD) : 222x93.25x56.5 mm
⊢	Weight : Around 0.53 Kg
⊢	Application : Indoor
⊢	Accessory : User Manual, Remote Control, USB 3.0 Cable
	Accessory : User Manual, Remote Control, USB 3.0 Cable

Best for BOOK NOW Video Conferencing



USB 3.0

TRAHD

VIDEO CONFERENCING



CAMERA FEATURES