**Online Classroom | Hybrid Classroom | Studio Setup | Video Conferencing** 



INTERACTIVE FLAT PANEL • OPS • PTZ CAMERA • ACTIVE LED • MICROPHONE

AUDIO PODIUM • DIGITAL PODIUM • DESKTOP VISUALIZER • DIGITAL SIGNAGE













**PRODUCT CATALOGUE** 





**INTERACTIVE FLAT PANEL** 

## MAXHUB **EDUCATION SERIES**

WITH NOTE WRITING SOFTWARE





**AUTHORISED PARTNER** 

android





## **Key Features**

- 4K ULTRA HD Resolution
- Android 11
- RAM : 4
- **STORAGE** : 32
- 40 Touch Points
- Inbuilt OPS

CPU : A55 x 4 RAM: 4 GB ROM : 32 GB

CPU : Core i5 / i7 RAM : 8GB / 16GB

Storage : 128GB / 256GB

GPU : Intel HD Graphics

Speaker Quantity : 2 Power : 2 x 12 W

- Anti Glare Glass Moha Level 7 hardness
- Eye Care Mode, Low Parallax, HDMI Out
- Shared USB Ports

**BUILT IN SYSTEM** 

PC MODULE Operating System : Windows 11 Gen

**Operating System : Android 11** 

DISPLAY	TOUCH SYSTEM
Size : 65 / 75 / 86 / 98 Inches	Glass Material : Anti-Glare Tempered
Display Ratio : 16:9	Touch Technology : Infrared
Backlight : DLED	Touch Point : 40 Points Touch
Resolution : ( 3840 x 2160 ) H x V	Writing Tools : Finger, Opaque Objects
Viewing Angle : ( H ) 178°, ( V ) 178 $^\circ$	Touch Accurancy : ± 1.5mm
SPEAKER	DISPLAY CONNECTORS

DISPLAY CONNECTORS
HDMI IN : 3
HDMI OUT : 1
VGA IN : 1
USB 2.0 : 1
USB 3.0 : 4
USB Touch Output : 2
RS232 : 1
RJ45 IN : 1
RJ45 OUT : 1

ENVIRONMENT REQUIREMENT Power : 100-240V-50 / 60 Hz Altitude : Below 5000 Mtrs Standby Power Consumption : < 0.5 W

#### **Best for** BOOK NOW **Online & Hybrid Classes**









**INTERACTIVE FLAT PANEL** 

**AI-TC 7500** 

WITH NOTE

WRITING SOFTWARE



# **TECHCART** Key Features

### • 4K ULTRA HD Resolution

- Android 14
- RAM : 4 / 8 GB
- STORAGE : 32 / 128 GB
- With OPS & Without OPS
- Front Audio Stereophonic Speakers
- Multiple Ports Input HDMI, VGA, Video, Touch
- IFR Touch Technology for Smooth Writing



**PRODUCT CATALOGUE** 





# Open Pluggable Specification OPS-PC Key Features

- Pre-Installed Windows 10 Pro / 11 Pro
- Processor : Intel® 10th/11th Gen Core™ i3 / i5 / i7
- 4K (3840 x 2160) Resolution
- 80 Pins Support
- Available in ASIAN and EURO

TECHNICAL SPECIFICATION		
Windows	10 Pro / 11 Pro	
Processor	Intel® Core™ i3 / i5 / i7	
Generation	10th / 11th Generation	
RAM	4 / 8 / 16 GB	
Storage	512 GB / 1 TB	
Support Pins	80 Pins	
USB	6	
HDMI	1	
Туре-С	1	
Display Port	1	
LAN	1	
Wifi	Yes	
Bluetooth	Yes	
Audio In / Out	Yes	
Power LED	Yes	
Wifi Antenna	2	
Restore Button	Yes	
Power Button	Yes	
Power Voltage	12V DC In	
Net weight	0.800 Gm	

## **Best for BOOKNOW** Online & Hybrid Classes





intel

CORE



intel.

CORE





www.techcartintegration.com





- 4K ULTRA HD ( 3840 x 2160 )@60fps
- 12X Optical Zoom, 16X Digital Zoom
- Al Tracking (Auto Tracking & Auto Framing)
- Double Streaming at the Same Time
- USB 3.0, HDMI, SDI, RS232, LAN, AUDIO IN
- Multiple Control Protocols
- Rich and Perfect Interface
- Multiple Presets (10 Presets by Remote)

CAMERA PARAMETER	USB CHARACTERISTICS
	Support Operating : Windows 7 / Pro, Windows 8, Windows 10,
Effective Pixels : 2.07 MP, 16:9	System Windows 11 / Pro, Windows XP, Mac OS, Linux
Viueo Foliliat . 3840x2180, 2372x1744, 2380x1440, 1720x1080,	Video Compression : H.265, H.264, MJPG USB Communication : UVC
	Protocol
Optical Lens : 12X Optical Zoom, f=4.4mm-52.8mm	INTERFACE & PROTOCOLS
View Angle : 8.8 ~ 68.8	Video Output : USB 3.0 Type – B
Iris : F1.8-2.6	Video Compression : H.264 AVC, H.264 SVC, H.265, MJPEG
Digital Zoom : 16X	Control Port : RS232 IN & OUT, RS485
Low Illumination : 0.5 Lux ( F 1.8, AGC ON )	Control Protocol : VISCA / Pelco-D / Pelco-P
DNR : 3D	Power Supply : HEC 3800 Outlet ( DC 12V )
White Balance : Auto / Manual / One Push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K	OTHER PARAMETER
/ 6500K / 7000K	Working Voltage : 12V
	Working Current : 0.25A ( Max )
	Power Consumption : 2.5W ( Max )
BLC : On / OFF	Storage Temperature : -40°C ~ 60°C -40°F ~ 140°F
WDR : OFF / Dynamic Level Adjustment	Working Temperature : -10°C~+40°C, 20%~80%
Video Adjustment : Brightness. Color, Saturation, Contrast, Sharpness. B/W mode. Gamma Curve	Dimension : 200mm x 176mm x 130mm ( W x H x D )
	Weight : 1.41 KG
Video SNR : >55dB	Usage : Indoor Only
PTZ PARAMETER	Package : Power Supply, USB 3.0 Cable, Remote Controller, User Manual
Pan / Tilt Rotation : -170° +170°,   -30° + 30°	Accessories Optional : Mount ( Extra Cost )
Pan / Tilt Controller Speed : 1.7~76 Second, 0.5~15 Second	
Preset Speed : Pan-60~Second, Tilt-30~Second	
Preset Numbers : 255 Presets ( 10 Presets by IR Remote )	
Best for	BOOK NOW
Destion	
	s / Video Conferencing /
Online / Hybrid Classe	s / Video Conferencing / ebcasting / Recording



TECHCART INTERACTIVE

TECHCAL

HYBRID CLASSROOM STUDIO SETUP



FHD PTZ CAMERA





## **Key Features**

- FULL HD ( 1920 x 1080 )@30fps
- 10X Optical Zoom
- Leading Auto Focus Technology
- Low Noise and High SNR
- Multiple Control Protocols
- USB 2.0, RS485, RS232 IN & OUT
- Low Power Sleep Function
- Multiple Presets (10 Presets by Remote)

CAMERA PARAMETER	USB CHARACTERISTICS
Image Sensor : 1/2.9 Inch High Quality CMOS Sensor	Support Operating : Windows 7 / Pro, Windows 8, Windows 10,
Effective Pixels : 2.07 MP, 16:9	System Windows 11 / Pro, Windows XP, Mac OS, Linux
Video Format : 1920x1080P @30fps/25fps, 1280x720P @30fps/25fps,	Video Compression : H.265, H.264, MJPG
1024x576P @30fps/25fps, 960x540P @30fps/25fps, 800x448P @30fps/25fps, 640x360P @30fps/25fps, 320x176P @30fps/25fps	USB Communication : UVC Protocol
Optical Lens : 10X Optical Zoom, f=4.34mm-41.66mm	INTERFACE & PROTOCOLS
View Angle : 8.8°~ 68.8°	Video Output : USB 2.0 Type-A
Iris : F1.7-3.0	Video Compression : H.265, H.264, MJPG
Digital Zoom : 10X	Control Port : RS232 IN & OUT, RS485
Low Illumination : 0.5 Lux ( F1.8, AGC ON )	Control Protocol : VISCA / Pelco-D / Pelco-P
DNR : 2D & 3DDNR	Power Supply : HEC 3800 Outlet ( DC 12V )
White Balance : Auto / Manual / One Push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K	OTHER PARAMETER
/ 6500K / 7000K	Working Voltage : 12V
Focus : Auto / Manual / One Push	Working Current : 0.25A ( Max )
Electronic Shutter : Auto / Manual	Power Consumption : 2.5W ( Max )
BLC : On / OFF	Storage Temperature : -10°C~+60°C, 20%~95%
WDR : OFF / Dynamic Level Adjustment	Working Temperature : -10° C~+50° C, 20%~80%
Video Adjustment : Brightness. Color, Saturation, Contrast, Sharpness, B/W mode, Gamma Curve	Dimension : 156.8mm x 112.6mm x 139.5mm ( W x H x D )
SNR : >50dB	Weight : IKG
	Usage : Indoor Only
PTZ PARAMETER	Package : Power Supply, USB 2.0 Cable, Remote Controller,
Pan / Tilt Rotation : -170°+170°, -30°+ 90°	User Manual
Pan / Tilt Controller Speed : 0.1~60 Second, 0.1~30 Second	Accessories Optional : Mount ( Extra Cost )
Present Speed : Pan-60~Second, Tilt-30~Second	
Preset Numbers : 255 Presets ( 10 Presets on IR Remote )	
Best for	BOOK NOW
Online / Hybrid Class	oc / Vidoo Conformation /
	es / Video Conferencing /
Live Streaming / W	lebcasting / Recording

AP-





HYBRID CLASSROOM STUDIO SETUP

**PRODUCT CATALOGUE** 

TECHCART INTERACTIVE

TECHCART .

SMART CLASSROOM SETUP





- 4K ULTRA HD ( 3840 x 2160 )@30fps
- 4K Intelligence Dual Lens Camera
- 12X Optical Zoom
- 110<sup>°</sup> Ultra Wide FOC
- 6 Microphones Arrays, 6 mtrs Audio Range
- Intelligent Voice Tracking
- Al Smart Framing
- USB 3.0 Plug and Play Camera

CAMERA PARAMETER
Camera Lens : 4K Intelligence Dual lens
Effective Pixels : 851M, 16:9
Video Format : 3840x2160, 2592x1944, 2560x1440, 1920x1080, 1280x720, 1024x576, 960x540, 800x448, 640x360 320x176
Optical Lens : 12X Optical Zoom, f=3.4mm-40.3mm
View Angle : 7.6 ~ 80.5 °
Iris : F1.8-2.6
Digital Zoom : 15X
Low Illumination : 0.5 Lux ( F 1.8, AGC ON )
DNR : 2D & 3D
White Balance : Auto / Manual / One Push / Specified Color Temperature
Focus : Auto / Manual / One Push
Video Adjustment : Brightness. Color, Saturation, Contrast, Sharpness, B/W mode, Gamma Curve
Video SNR : >55dB
Paranormic Lens : Fixed Focus
Iris : F2.0+5%
Focus : F=1.89mm

INTERFACE
Back Panel : HDMI, LAN, USB 3.0, A-In, RS232-In, DC 12V Power
Video Output : USB 3.0, HDMI, LAN
Video Compression : LAN - H.264, H.265, USB - H.265, MJPEG
Control Port : RS232 IN
Control Protocol : VISCA / Pelco-D / Pelco-P
Power Supply : HEC 3800 Socket ( DC 12V )
Audio Input : Dual Channel 3.5mm Linear Input
Audio Output : HDMI, LAN, USB 3.0
Audio Compression : ACC, MP3, G.711A
Network Protocols : RTSP, RTMP, ONVIF, GB/T28181, VISCA OVER IP,
IP VISCA, RTMPS, SRT, Support remote
upgrade, Remote restarting and Remote reset
Power Adapter : Input - AC 110V~AC 220V
Output - DC 12V / 2.5 A
OTHER PARAMETER
Rotating Angle : Pan +110~ Tilt30~+30
Control Speed : Pan 0.1/s~100/s Tilt 0.1/s~70/s
Smart Framing : Group Framing, Face Detection
Voice Tracking : Voice Localization, Voice Tracking On/Off

Smart Framing : Group Framing, Face Detection Voice Tracking : Voice Localization, Voice Tracking On/Off Microphone : 6 Mics arrays with 6meters audio range Product Dimensions : 220x114x159 mm (L x W x D)





6 METERS AUDIO RANGE



#### PANORAMIC + CLOSE UP LENS





- FULL HD ( 1920 x 1080 )@60fps
- 20X Optical Zoom
- Leading Auto Focus Technology
- Low Noise and High SNR
- Multiple Control Protocols
- HDMI, SDI, LAN
- Low Power Sleep Function
- Multiple Presets (10 Presets by Remote)

CAMERA PARAMETER	USB CHARACTERISTICS
	Support Operating : Windows 7 / Pro, Windows 8, Windows 10,
Effective Pixels : 2.07 MP, 16:9	System Windows 11 / Pro, Windows XP, Mac OS, Linux
Video Format : 1920x1080P @60fps/25fps, 1280x720P @60fps/25fps, 1024x576P @60fps/25fps, 960x540P @60fps/25fps,	Video Compression : H.265, H.264, MJPG USB Communication : UVC
800x448P @60fps/25fps, 640x360P @60fps/25fps, 320x176P @60fps/25fps	Protocol
Optical Lens : 20X Optical Zoom, f=5.5mm-110mm	INTERFACE & PROTOCOLS
View Angle : 8.8°~ 68.8°	Video Output : USB 2.0 Type-A
Iris : F1.7-3.0	Video Compression : H.265, H.264, MJPG
Digital Zoom : 10X	Control Port : RS232 IN & OUT, RS485
Low Illumination : 0.5 Lux ( F1.8, AGC ON )	Control Protocol : VISCA / Pelco-D / Pelco-P
DNR : 2D & 3D DNR	Power Supply : HEC 3800 Outlet ( DC 12V )
White Balance : Auto / Manual / One Push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K	
/ 6500K / 7000K	OTHER PARAMETER
Focus : Auto / Manual / One Push	Working Voltage : 12V
Electronic Shutter : Auto / Manual	Working Current : 0.25A ( Max )
BLC : On / OFF	Power Consumption : 2.5W ( Max )
WDR : OFF / Dynamic Level Adjustment	Storage Temperature : -10°C~+60°C, 20%~95%
Video Adjustment : Brightness. Color, Saturation, Contrast,	Working Temperature : -10° C~+50° C, 20%~80%
Sharpness, B/W mode, Gamma Curve	Dimension : 150mm x 150mm x 167.5mm
SNR : >50dB	Weight : 1.4 KG
	Usage : Indoor Only
	Package : Power Supply, USB 3.0 Cable, Remote Controller, User Manual
Pan / Tilt Rotation : -170°+170°, -30°+ 90°	
Pan / Tilt Controller Speed : 0.1~60 Second, 0.1~30 Second	Accessories Optional : Mount ( Extra Cost )

Present Speed : Pan-60~Second, Tilt-30~Second Present Numbers : 255 Presets (10 Presets on IR Remote )

**Best for** 

11400 01	ripati eee ne ijpe ii
Video Co	ompression : H.265, H.264, MJPG
Control	Port : RS232 IN & OUT, RS485
Control	Protocol : VISCA / Pelco-D / Pelco-P
Power S	upply : HEC 3800 Outlet ( DC 12V )
(	OTHER PARAMETER
Working	Voltage : 12V
Working	Current : 0.25A ( Max )
Power C	onsumption : 2.5W ( Max )
Storage	Temperature : -10°C~+60°C, 20%~95%
Working	Temperature : -10° C~+50° C, 20%~80%
Dimensi	on : 150mm x 150mm x 167.5mm
Weight :	1.4 KG
Usage : I	ndoor Only
Package	: Power Supply, USB 3.0 Cable, Remote Controller, User Manual



WIRELESS MIC FHD PTZ CAMERA TECHCART INTERACTIVE FLAT PANEL VIRTUAL SMART CLASSROOM & TECHCART **REMOTE TRAININGS** INTERACTIVE FLAT PANEL DISPLAY STAND HYBRID CLASSROOM STUDIO SETUP

### **Online / Hybrid Classes / Video Conferencing /** Live Streaming / Webcasting / Recording



#### SMART CLASSROOM SETUP

#### **PRODUCT CATALOGUE**

) 🖬 🕆 🍈 🚐 🗋

1080P ULLHD



**Pro Series** 



# **Key Features**

- 4K ULTRA HD (3840 x 2160)@30fps
- EPTZ & 10X Digital Zoom
- Built in Mic with unique Noise Suppression
- Al-powered Auto Framing & Face Detection
- Wide FOV : 83°/100° Wide Angle
- Wide Application for Video Conferencing
- Low Noise & High SNR
- Plug and Play with USB 3.0

CAMERA PARAMETER
Sensor : 1/2.8 Inch High Quality 4K CMOS Sensor
Effective Pixels : 8.28MP 16:9
Video Output : 1 Channel USB 3.0, Type B, Audio In
Audio Input : 2 Built In Mic Pickup
Video Format : 3840x2160, 2592x1944, 2560x1440, 1920x1080,
1280x720, 1024x576, 960x540, 800x448, 640x360
320×180
Digital Zoom : 10X
View Angle : 110°(D) / 100°(H) / 53°(V)
Focus : f=3.24mm
Aperture : F2.1
Minimun Illumination : 0.1Lux ( F 1.8, AGC ON )
Focus : Manual
White Balance : Auto / Manual
Exposure : Auto / Manual
Backlight Contrast : On / Off
SNR : >50dB

USB FEATURES
Operating System : Windows 7, Windows 10, Windows 11
MacOS, Linux ( Support UVC )
Video Format : YUY2, MJPG, NV12, H.264
USB Audio : Support
USB Protocols : UVC, UAC
PTZ Control : Support EPTZ
Hardware Requirement : 2.4GHz Intel Core Duo Processor
or Higher " 2GB RAM or more "
USB 2.0, ( USB 3.0 for 4K )
OTHER PARAMETERS
OTHER PARAMETERS
Input Voltage : 5V
Input Voltage : 5V Input current : 1A ( max )
Input Voltage : 5V Input current : 1A ( max ) Power Consumption : 5W ( max )
Input Voltage : 5V Input current : 1A ( max ) Power Consumption : 5W ( max ) Store Temperature : -10 Ç ~ +60 Ç
Input Voltage : 5V Input current : 1A ( max ) Power Consumption : 5W ( max ) Store Temperature : -10 Ç ~ +60 Ç Store Humidity : 20% - 90%
Input Voltage : 5V Input current : 1A ( max ) Power Consumption : 5W ( max ) Store Temperature : -10 Ç ~ +60 Ç Store Humidity : 20% - 90% Working Temperature : -10 C - +50 C

OTHER PARAMETERS
Input Voltage : 5V
Input current : 1A ( max )
Power Consumption : 5W ( max )
Store Temperature : -10 Ç ~ +60 Ç
Store Humidity : 20% - 90%
Working Temperature : -10 C - +50 C
Working Humidity : 20% – 80%
Dimension ( WxHxD ) : 180 x 42.5 x 46.3mm
Weight : Around 0.3 Kg
Application : Indoor
Accessory : User Manual, Remote Control, USB 3.0 Cable

BOOK NOW

## **Best for Online / Hybrid Classes / Video Conferencing /** Live Streaming / Webcasting / Recording





**VIDEO CONFERENCING** 



#### **CAMERA FEATURES**





- FULL HD ( 1920 x 1080 )@30fps
- EPTZ and 4X Digital Zoom
- 88° wide field of view
- Built in 2 Microphones 1+ mtr Voice Pickup
- Noise Canceling Technology
- Adjustable Video Settings, Brightness, Etc
- Support all Major third-party Platforms
- USB 2.0 Plug add Play

•	•••		) –	•••	CAMERA
		ТЕСНСА	RT	_	





CAMERA PARAMETER
Image Sensor : High Quality CMOS Sensor
Effective Pixels : 2 MP, 16:9
Video Format : 960x540, 320x180, 432x240, 640x360, 800x448, 800x600, 864x480, 960x720, 1024x576, 1280x720, 1600x897, 17920x180a, 272x144, 368x208, 384x216, 480x272, 624x352, 912x512
USB : USB 2.0 ( for power and firmware upgrade )
View Angle : 88 ( D ) / 80 ( H ) / 50 ( V )
Compatible : Support all major third-party platform
Low Illumination : 0.5 Lux ( F 1.8, AGC ON )
Lens Focus : Fixed
Distance Range of Lens : 0.3m - 1.7m
Backlight Contrast : On / Off
Anti-Flicker : Manual
Video Adjustment : Brightness / Resolution / Saturation /
Contrast / Gain / Low-light / Exposure
White Balance

SNR : >50dB
Input Voltage : 5V
Input Current : 500mA ( max )
Power : 2.5W ( max )
Temperature : Storage : -10 C - +60 C
Operating : -10 C - +50 C
Humidity : Storage : 20% - 95%
Operating : 20% - 80%
Cable Length : 1.8 meters
Dimension : 102x46x30 mm
Weight : 0.15 Kg

CAMERA PARAMETER







**VIDEO CONFERENCING** 



**CAMERA FEATURES** 





- Built in 3 Subwoofers and 1 Tweeter 60 Watt
- Gooseneck Microphone
- LED Reading Lamp
- **1 Handheld and 1 Collar Microphone**
- Built in Control Panel and 24V Phantom
- Smart and Robust Design
- 1 Aux Input Control
- Short Circuit Clipping and High Temp **Protection**

TECHNICAL SPECIFICATION		
Power Output	60 Watts	
Input Channels	Mic-1 (Gooseneck Mic) 8mV, Mic-2 : 4mV, Line-100mV, AUX-200mV	
Frequency Response	50 – 16,000Hz	
Tone Control	Bass $\pm 5$ dB at 100Hz, Treble $\pm 5$ dB at 10k Hz	
MIX Output	775mV	
Digital Player	MP3 Recorded Player with USB, SD, MMC Card & Bluetooth	
USB Charger Outlet	DC-5V, 1A	
External Speaker Impedance	$4\Omega$ to $8\Omega$	
Power Supply	AC 220-240V, 50/60Hz	
Power Comsumption	AC 100VA	
Dimensions	L580 x W420 x H1100 mm	
Weight	30 kg	
Microphone	1 Handheld and 1 Collar Microphone	
Microphone Element	Dynamic, Cardioid	
Transmission Distance	15-30 Meters	
RF Output Power	15mW	
Frequency Response	50 – 15,000Hz	
Power Requirement	3V (2x1.5V AA Pencil Cells)	
Current Consumption	<100 mA	
Weight ( w/o Battery )	180 gm	

#### **Best for BOOK NOW Teaching / Training / Meeting**







HANDHELD MIC 8











## **Multimedia Digital Podium TCDP-1099**









TOUCH MONITOR



Cordless Handheld Microphone : 1

Amplifier : Dual Channel 60W / 80W / 100W Speaker : Wall Mount Speaker (20x2 / 4 / 6 ) Watt Each

**Best for** 

Collar Cordless Microphone : 1











AMPLIFIER WITH MIC

Lecture / Conference Room



PODIUM CONTROLLER



## **Key Features**

- One Stop Solution for Modern Day
- Touch Screen with Sliding Lockable Cover
- Motorised Up-Down & Stop Panel
- Built in Audio Complete System
- Built in Latest Configuration CPU (Opt)

Pen Touch Features Resolution : 1920 x 1080 FHD Dynamic Contrast ratio : 50M:1 Brightness : 200cd/m<sup>2</sup> (typ)

Lockable Wheels

- Built in Digital Visualizer ( Opt )
- Built in Central Controller
- Built in Wheels for Easy Movement

METALLIC BODY
Mild Steel with locable wheels
Sliding Top opening can be used as a laptop tray acting as shelves for supporting extra equipments ( Laptop or documents camera ) with Lock in the Centre
Doors with Lock
Storage Rack with Lock
Keyboard & Mouse tray
With Wheels
External Connectors on the side
VGA - 1, USB - 1, RJ45 - 1, To Connect Laptop, Documents Camera USB, Etc
SYSTEM DETAILS
Chasis : Industrial Grade Aluminium Chasis
Chasis . Industriat Grade Aluminium Chasis
Processor : i3 / i5 / i7 ( 11th Generation )
Processor : i3 / i5 / i7 ( 11th Generation )
Processor : i3 / i5 / i7 ( 11th Generation ) Memory : 4GB / 6GB / 16GB
Processor : i3 / i5 / i7 ( 11th Generation ) Memory : 4GB / 6GB / 16GB HDD / SSD : 256GB / 512GB / 1TB
Processor : i3 / i5 / i7 ( 11th Generation ) Memory : 4GB / 6GB / 16GB HDD / SSD : 256GB / 512GB / 1 TB Operating System : Window 11 Pro
Processor : i3 / i5 / i7 (11th Generation ) Memory : 4GB / 6GB / 16GB HDD / SSD : 256GB / 512GB / 1TB Operating System : Window 11 Pro Minimum Range : 15 Meters
Processor : i3 / i5 / i7 (11th Generation ) Memory : 4GB / 6GB / 16GB HDD / SSD : 256GB / 512GB / 1TB Operating System : Window 11 Pro Minimum Range : 15 Meters Power Supply : 100-240V, 50HZ, AC Supply Provision for : A dedicated space to house CPU/Laptop Additional with Security Lock Tray, Sliding Shelf for

Colors : 16.7M Aspect Ratio : 16.9 Interface : USB Refresh Rate : 60 Hz VGA:1 USB 3.2 Type - A Down Stream:2 USB 3.2 Type - B Up Stream:1 3.5mm Audio In:1 3.5mm Audio Out:1 HDM11.4:1 Direlay Dect:1 Display Port : 1 CENTRAL TOUCH CONTROL SYSTEM Projector : On Projector : Off Screen : Up Screen : Down Volume : Up Volume : Down Volume : Mute Source Selection : Computer Laptop, Visualizer, DVD/VCR Microphone Control - Gooseneck x 2 Microphone Control - Cordless DVD/VCR - Controls Play, Forward, Rewind, Stop, Pause, Recording Front Logo

INTEGRATED INTERACTIVE PANEL Interactive Panel with Motorised Angle Adjustment / Tilt / Up & Down movement by Button / Switch 22" Inch, 10 Point Touch Screen Monitor, Finger Touch &

**PRODUCT CATALOGUE** 

DOCUMENT CAMERA





# **Digital Signage**

# **Digital Signage**



# **Key Features**

- 55" Floor Mount Non-Touch Metal Body signage
- 4K Ultra HD Resolution
- Wide Viewing Angle of 178°
- 4mm, MOHS 7 Grade Tempered Glass, Shatter Proof
- Including pictures, audio, video, PDF, Etc
- Built in Android and DSS Apk
- Works with LAN, Wifi

**Best for** 

- 3-level check of programs, and schedules
- Built for 24x7 Performance with 60000hrs Screen Life
- Eco LED backlit for Power Saving
- DSS Management Software to manage <200pcs DSS Players



Scan to Order







**BOOK NOW** 





# **Active LED**

# **Key Features**

- 4K Ultra HD Resolution
- 100,000 hours of 24/7 Operation
- Multiple Support MP4, JPG, PNG, PDF, PPT
- Support HDMI, USB
- High Quality Indoor and Outdoor LED Display
- Split Screen to showcasing different Ads
- Increased reliability easier to maintain and have a longer life with the latest technology
- Complete front access for easy installation and service
- Full range of optional processing and content management technologies
- Includes necessary video wall controllers with scaling and image processing
- On-board redundant power supply with automatic failover to maximize uptime

# Best for Commercial Advertisement





**PRODUCT CATALOGUE** 













- Effective Pixels >500/800 Millions
- Fixed Focus ( Digital Zoom )
- Built in High Sensitivity Digital Microphone
- Vertical and Horizontal Shooting Direction
- A4 and A3 Sizes
- Touch Sensors
- Power <2W
- USB Plug and Play

SPECIFICATIONS			
Effective Pixels	500 / 800 Pixels ( Optional )		
Focusing Method	Fixed Focus ( Digital Zoom )		
Definition	100 Lines		
White Balance	Automatic		
Frame Rate	15 Frames ( 3264 x 2448 ) / 20 Frames ( 2592 x 1944 ) / 30 Frames ( 1920 x 1080 )		
Shooting Range	A4 ( 310 x 220 ), A3 ( Optional )		
Port	DC 5V / USB Output, 3.0 B Port 1		
Output	USB 3.0 MJPG		
3D Noise Reduction	Yes		
Physical Button Function	No		
Illumination	High Brightness LED x 10 Grains, Brightness Level : Level 3 , Touch		
Lightning Control	Four Level Cycle Control of Touch Support		
Recording	Built in High Sensitivity Digital Microphone		
Power	USB 5V		
Net Weight	<2W		
Gross Weight	1 KG		
Packing Specification	12cm x 22cm x 46cm (Width x Height x Length)		
Packing Enclosure	Warranty Card, Certification of Conformity, 2m A/B Cable, Document Pad		
Cabinet Material	Aluminium Alloy + Environmentally Friendly ABS Plastic		
Body Specification	10cm x 9.5cm x 32.5cm (Width x Thickness x Height)		
Expanded Size	10cm x 27cm x 32.5cm (Width x Thickness x Height)		
Software	Random Software Teaching Booth V2.0 Version		
Software Function	Annotation, Same-Screen Comparison, Partial Reading, 360 Rotation, Picture-in-Picture, Etc		
Software Language	Simplified Chinese ( English Version Available )		

# Best for Boo





LEADING EDUCATIONAL MULTIMEDIA TECHNOLOGY AND SOLUTION PROVIDER TCDC - 550

SMART CLASSROOM





**GK-9802** 



# **Key Features**

- 8 Mega Pixels
- 10x Digital AI Zoom
- 32 Images Storage
- Auto Focus
- Double Side LED and Base Light
- Inputs HDMI, VGA, Video, Audio ( Opt )
- Outputs HDMI, VGA, Video
- Remote Control and Touch Control Panel
- One Button Adjustment, Image Freezing
- Split Screen, Automatic White Balance

#### **SPECIFICATIONS**

Lens	22-26x Optical Zoom, 10x Digital Al Zoom, 8 Mega Pixels
Storage	32 Images
Focus	Automatic
Shooting Range	A4 and A3 Sizes
Light	Double Side LED Light, Base Light
Input	( Standard Version ) VGA, 1 Video, 1 Audio ( Optional ) USB - 1 /
mpor	( HD Version ) VGA, 1 HDMI, 1 USB
Output	( Standard Version ) VGA, 1 Video, 1 Audio ( Optional ) USB - 1 /
output	( HD Version ) VGA, 1 HDMI, 1 USB
Control	RS-232, USB
Definition	1200 TV Line
Net Weight	5KG
Gross Weight	6.5KG
Product Size	470x370x135mm ( Closed ) / 410x375x550mm ( Opened )
Packaging Size	440x200x550mm
Control Mode	Remote Control
Disited Eurotian	Mirror / Color - Black & White / Rotation / One Button Adjustment /
Digital Function	Slit Screen / Image Freeze / Color Adjustment / Automatic WhiteBalance

## **Best for** Teaching / Smart Classes







Scan to Order







**PRODUCT CATALOGUE** 



# SENNHEISER



## **Promoted by Techcart**

0



# **Key Features**

- Clip-on Microphone & Bodypack Transmitter
- Antenna-switching Diversity Reception
- Integrated Antennas
- Auto frequency Management & Synchronization via Remote Channel for Easy Setup
- UHF Frequencies within a Large Bandwidth
- Upto 10 Compatible Channels
- Easy-to-use Wireless Collar Microphone

SPECIFICATIONS
Max Sound Pressure Level : 130dB SPL
Sensitivity in Free Field, No Load : 1.6mV/Pa
Frequency Response : 50Hz-16kHz
Frequency Range : 548-572 MHZ
Simultaneous Channels : Up to 10 Channels
Operating Range : 250 ft Line of Sight
Microphone Included : YES
Microphone Type : Condenser
Channel Selection : Automatic
Polar Pattern : Cardioid
Connection Cable : Locking mini-jack
Microphone Cable Longth : 5 2ft

Microphone Cable Length : 5.2ft

Signal/Noise Ratio : >103dB

Dimensions : 7.87 x 1.65 x 5 Centimeters

## Best for BOOKN Online Classes / Audio Recording







**PRODUCT CATALOGUE** 







BODYPACK TRANSMITTER





# SENNHEISER XSW1-ME3



## **Promoted by Techcart**

0

**HEADSET MIC** 

**PRODUCT CATALOGUE** 



- Light Weight Headmic & Bodypack Transmitter
- Antenna-switching Diversity Reception
- Integrated Antennas
- Auto frequency Management & Synchronization via Remote Channel for Easy Setup
- UHF Frequencies within a Large Bandwidth
- Upto 10 Compatible Channels
- Easy-to-use Wireless Headset System

SPECIFICATIONS
Max Sound Pressure Level : 150dB SPL
Sensitivity in Free Field, No Load : 1.6mV/Pa
Frequency Response : 50Hz-16kHz
Frequency Range : 548-572 MHZ
Simultaneous Channels : Up to 10 Channels
Operating Range : 250 ft Line of Sight
Microphone Included : YES
Microphone Type : Condenser
Channel Selection : Automatic
Polar Pattern : Cardioid

Connection Cable : Locking mini-jack

Microphone Cable Length : 1.6 Meters

Signal/Noise Ratio : >103dB

Dimensions : 34.8 x 34.5 x 8.6 Centimeters

## Best for





**Online Classes / Audio Recording** 





BODYPACK TRANSMITTER

**RECEIVER FRONT** 

# **TECHCART WAMAHA YVC-200**



# **Key Features**

- Yamaha's professional Quality DSPs
- Super Wideband Audio for ample, Clear Sound
- 360 and max radius 2m Mic Pick up Range
- Maximum 88dB Loud Speaker Volume
- USB Connection for Laptop
- Bluetooth/NFC Connections for phones & Tablets
- Rechargeable Battery for Upto 10 hours use
- User Frienly Touch Sensor Buttons




## **Promoted by Techcart**



**HD** Audio

Recommended Use : Up to 4 People         Interfaces : USB 2.0 Full Speed (Mini-B), Bluetooth, NFC (Near field Communication), 3.5mm Headset Jack (Stereo Out/Monaural In)         Connectable : USB computer running windows or Devices macOS         Bluetooth : Smartphone running Android or iOS         Power Sources : USB bus power         Maximum Power Consumption : 2.5W         Dimensions (WxHxD) : 140x43x140mm         weight : 0.28 Kg         Color : Black, White         Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later         Bluetooth : Version 4.2         NFC : Compatible to Android devices         Accessories : USB Cable Im, User Manual, Carrying case         Operating : Temperature 0 to 40 C         Environment Humidity 20 to 85% (No Condensation)         Storage : Temperature -20 to +50 C		GENERAL
NFC ( Near field Communication ), 3.5mm Headset Jack (Stereo Out/Monaural In) Connectable : USB Computer running windows or Devices macOS Bluetooth : Smartphone running Android or iOS Power Sources : USB bus power Maximum Power Consumption : 2.5W Dimensions ( WxHxD) : 140x43x140mm weight : 0.28 Kg Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Recomme	ended Use : Up to 4 People
3.5mm Headset Jack (Stereo Out/Monaural In)         Connectable : USB Computer running windows or         Devices       macOS         Bluetooth : Smartphone running Android or iOS         Power Sources : USB bus power         Maximum Power Consumption : 2.5W         Dimensions ( WxHxD) : 140x43x140mm         weight : 0.28 Kg         Color : Black, White         Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later         Bluetooth : Version 4.2         NFC : Compatible to Android devices         Accessories : USB Cable 1m, User Manual, Carrying case         Operating       Temperature 0 to 40 C         Environment       Humidity 20 to 85% ( No Condensation)	Interface	s : USB 2.0 Full Speed ( Mini-B ), Bluetooth,
Connectable : USB Computer running windows or Devices macOS Bluetooth : Smartphone running Android or iOS Power Sources : USB bus power Maximum Power Consumption : 2.5W Dimensions (WxHxD) : 140x43x140mm weight : 0.28 Kg Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)		NFC (Near field Communication),
Devices macOS Bluetooth : Smartphone running Android or iOS Power Sources : USB bus power Maximum Power Consumption : 2.5W Dimensions (WxHxD) : 140x43x140mm weight : 0.28 Kg Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)		3.5mm Headset Jack (Stereo Out/Monaural In)
Bluetooth : Smartphone running Android or iOS Power Sources : USB bus power Maximum Power Consumption : 2.5W Dimensions (WxHxD) : 140x43x140mm weight : 0.28 Kg Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Connecta	ble : USB Computer running windows or
Power Sources : USB bus power Maximum Power Consumption : 2.5W Dimensions ( WxHxD) : 140x43x140mm weight : 0.28 Kg Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Devices	macOS
Maximum Power Consumption : 2.5W Dimensions ( WxHxD) : 140x43x140mm weight : 0.28 Kg Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Bluetooth	n : Smartphone running Android or iOS
Dimensions ( WxHxD) : 140x43x140mm weight : 0.28 Kg Cotor : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Power So	ources : USB bus power
weight : 0.28 Kg Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Maximum	n Power Consumption : 2.5W
Color : Black, White Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Dimensio	ons ( WxHxD) : 140x43x140mm
Support OS : Windows 11, Windows 10, Windows 7, Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	weight : 0	).28 Kg
Mac OS 10.14, Mac OS 10.13, Mac OS 10.12, USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Color : Bl	lack, White
USB 2.0 or later Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Support (	OS : Windows 11, Windows 10, Windows 7,
Bluetooth : Version 4.2 NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)		Mac OS 10.14, Mac OS 10.13, Mac OS 10.12,
NFC : Compatible to Android devices Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)		USB 2.0 or later
Accessories : USB Cable 1m, User Manual, Carrying case Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	Bluetooth	n : Version 4.2
Operating : Temperature 0 to 40 C Environment Humidity 20 to 85% ( No Condensation)	NFC : Cor	mpatible to Android devices
Environment Humidity 20 to 85% ( No Condensation)	Accessor	ries : USB Cable 1m, User Manual, Carrying case
, , , ,		
Storage : Temperature -20 to +50 C	Environm	nent Humidity 20 to 85% ( No Condensation)
	5	
Environment Humidity 10 to 90% ( No Condensation )		
Others : Auto standby energy-saving function,		
Firmware update, Security slot	F	Firmware update, Security slot





### Audio / Video Conferencing for Small Room





WIRELESS VIDEO CONFERENCING

# TECHCART WAMAHA YVC-330

**Promoted by Techcart** 



# **Key Features**

- Comfortable Meeting in a Noisy Environment
- Light Weight Design Powered by USB
- Echo Canceller and Clear Conversation
- 3 Microphones with Human Voice Detection
- USB Powered Rich Speakers Volume
- Daisy Chain 2 Units for Medium Sized Room
- Plug and Play, Bluetooth, NFC and Audio In/Out
- Compatible with any UC Applications

GENERAL
Interfaces : USB 2.0 Full Speed ( Mini-B ), Bluetooth,
NFC (Near field Communication),
EXT In/Out ( Stereo mini plug )
Connectable : USB Computer running windows or
Devices macOS
Bluetooth : Smartphone running Android or iOS
Power Sources : USB bus power
Maximum Power Consumption : 2.5W
Dimensions ( WxHxD) : 235x46x226mm
weight : 0.8 kg
Color : Black
Support OS : Windows 10, Windows 8.1, Windows 7,
Mac OS 10.14, Mac OS 10.13, Mac OS 10.12,
USB 2.0 or later
Bluetooth : Version 2.1 + EDR
NFC : Compatible to Android devices
Accessories : USB Cable 3m, User Manual
Operating : Temperature 0 to 40 C
Environment Humidity 20 to 85% (No Condensation)
Storage : Temperature -20 to +50 C
Environment Humidity 10 to 90% ( No Condensation )
Others : Firmware update
( Transfered from x3, 360 coverage )

AUDIO			
Microphone : Undirectional microphones x3, 360 Coverage			
Speaker : Full-range speaker x 1			
Volume : Momentary maximum 91dB ( 0.5 m )			
Frequency Bandwidth : 190 Hz to 20,000 Hz			
Signal Processing : Adaptive echo canceller, Noise			
reduction, Auto tracking,			
Auto gain control, dereverberation,			
Sound cap			
Standard mode : Pick-up the sound in small-medium			
conference rooms			
Sound cap : Auto mute distracting noise in open work			
place and deliver only the sound from the			
pick-up range ( Radius of 1 m )			
* 2 units daisy chain connection is available			
on Standard Mode			

OPTIONAL ACCESSARY
Daisy chain cable ( Product number : YCBL-DC3M,

Cable length-3m, Terminal shape-stereo mini plug x2 )










VIDEO CONFERENCING



# TECHCART WAMAHA YAMAHA YVC-1000







## **Key Features**

- Comfortable Meeting in a Noisy Environment
- Light Weight Design Powered by USB
- Echo Canceller and Clear Conversation
- 3 Microphones with Human Voice Detection
- USB Powered Rich Speakers Volume
- Connect 5 Microphones Units
- Plug and Play, Bluetooth, NFC and Audio In/Out
  Compatible with any UC Applications

·			
ĺ	GENERAL		
	Interface : Control unit USB 2.0 High Speed, Bluetooth,		
Audio Input/Output terminal ( stereo RCA pin ),			
	External speaker terminal ( RCA pin ) x2		
Power terminal, Microphone terminal			
Microphone Input/Output terminals			
Power consumption : 20W ( One Connected Microphone )			
35W (Five Connected Microphones)			
Radio Interface : FCC ( Part 15B ) Class A, ICES-003			
	standard		
Operating environment : Temperature – 0 to 40 C			
Humidity – 20 to 85%			
	Dimensions : Control unit (WxHxD) 332x95x165 mm		
Microphone (WxHxD) 136x36x136) mm			
Weight : Control unit 1.8 Kg			
Microphone 0.4 Kg			
Power source : 120V ( 60Hz )			
Support OS : Windows 10, Windows 11, USB 2.0, USB 3.0			
or later			
Bluetooth : Version 2.1 + EDR			
	Maximum distance 10m		
	NFC : Compatible to Android devices		
ĺ	Accessories : Power cable 3m, USB cable 5m,		

Microphone cable 5m, Quick Start Guide


62 mm (6-3/8

Top side

Control Unit

Microphone


136 mm (5-3/8")



AUDIO

Microphone : Undirectional microphones x 3





**PRODUCT CATALOGUE** 

332 mm (13-1/16")

Front

Control Unit





# **Floor Stand**

# **Key Features**

- Interactive Panel / TV Size 55"-110"
- Strong heavy duty material
- Loading Capacity 120 Kgs
- Laptop / Camera VC Shelf Yes
- TV Height Adjustable
- Swivel Base 4 Wheels for Easy Movement

#### **TECHNICAL SPECIFICATION**

TV Size Support	55" to 110"
Load Capacity	120KG
Shelf	Yes
Height Adjustable	Yes
Lockable Caster wheels	Yes
Wheel Lock	Yes
360 Swivel Caster Wheels	Yes
Product Size	1330 x 660 x 1820 mm
VESA Supported	900 x 600









Interactive Flat Panel Display














## **Podcast Studio**

## **Features of Podcast Studio Setup**

- Professional Studio Setup
- Easy to Use
- Spacious & Comfortable
- Professionally Equipped
- Budget-friendly Option
- Soundproof Room
- Soundproof Wall Layer
- Soundproof Ceiling and Floor
- Professional Acoustic Interior
- Superior Sound Quality
- Live Stream Podcast on Multiple platform at the same time



## **Techcart Offered Products**



FHD WEB CAM



WIRELESS HEADBAND MIC



SPEAKERPHONE (SMALL ROOM)



WALL SPEAKER



INDOOR ACTIVE LED



**E-LECTURN** 



**ACTIVE 3.0 USB EXTENTION** 



FLOOR STAND



**4K WIDE ANGLE** CAMERA



WIRELESS COLLAR MIC WITH HANDHELD MIC



SPEAKERPHONE (LARGE ROOM)



**CEILING SPEAKER** 



OUTDOOR ACTIVE LED



**AUDIO PODIUM** 



HDMI CABLE EXTENTION



**HEAVY DUTY** FLOOR STAND



20X FHD PTZ CAMERA



WIRELESS HEADBAND MIC



SPEAKERPHONE (EX-LARGE ROOM)



DSP NCD



DIGITAL SIGNAGE



DESKTOP VISUALIZER



SPLITTER



TRIPOD





**VOICE TRACKING 4K PTZ CAMERA** 



TABLE TOP MIC



DEEP ECHO CANCELLATION SPEAKERPHONE





TECHCART CONTROLLER



DOCUMENT CAMERA



AMPLIFIER CABLE



## **Our Happy Teachers, Schools & Institutions**



